

Novaplus T380 Ag

ACL CODES - MINI : 9712021 ; NORMAL : 9712015 ; MAXI : 9712009

Description

Intrauterine Device with a "Y" shaped structure which can be completely inserted into the cannula by pulling the threads. It has a 380 mm² copper wire spiral with a silver core. Comes in three sizes.

Contraceptive. Sterile single use product.



Mini

Normal

Maxi

Technical Data

COMPONENT	COMPOSITION	DIMENSIONS			
		Reference	Size	Width	Length
IUD Structure	Polyethylene	9712015 9712021 9712009	- Normal - Mini - Maxi	31 mm 24 mm 36.5 mm	33 mm 30.5 mm 38 mm
Wire	Copper purity > 99,99%	Diameter	Length	Surface	Silver core diameter
		0.4 mm	302 mm	380 mm ²	0.1 mm
Removal thread	Polyethylene	Diameter 0.25 mm Length 280x 2 mm			
Rod	Polypropylene	Diameter 2 mm Useful Length 200 mm			
Insertion cannula	Polyethylene	External Diameter 3.8 mm Length 195 mm			
Top gauge	Silicone and Polypropylene	Width 7.9 mm Length 12.7 mm Height 6.6 mm			

Sterilization procedure

Ethylene oxide

Insertion procedure

By expulsion of the IUD from the cannula in the uterus through the insertion tube.

Packaging

Single package

Recommended time in place

5 years